

FLOS

07.9630.AP Polished Aluminium/Anodized Aluminium

Light Bell

Designed by Piero Lissoni, 2013



Suspended luminaire for mounting on the ceiling with LED light source. (4 metres maximum distance to ceiling). Power supply source integrated into luminaire housing.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Suspension
Environments	Indoor dry location
Iicos	No
Number of heads	1

Physical

Colour	Polished Aluminium/Anodized Aluminium
Trim	No
Orientation	Fixed
Net weight (kg)	0.95
IP internal	20
IP external	20




Download

[Mounting instructions](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric


Electrical

Insulation class	I
Frequency (Hz)	0
Dimmable	No
Emergency type	No

Notes

Pin-block type dissipater. Please ask us for a higher IP.

Accessories & Power Supply



OPTIONAL Accessory

08.8775.40

Rosette. IP20



OPTIONAL Accessory

F0557020

Rosette for indoors. IP20.
Dimmable Push/Dali



OPTIONAL Accessory

F0556020

Light Bell Canopy Power supply
for standard and dimmable
versions