



PRODUCT SPECIFICATION

GENERAL

| | | | |
|----------------------------------|--------------------|------------------------|---|
| FINISH: | Matt Black | CABLE LENGTH: | Not Applicable |
| MAIN MATERIAL: | Metal - Mild Steel | GROSS WEIGHT: | 0.14 (Kg) |
| DIMENSIONS: | D: 130mm D: 82mm | CLASS: | CE (Class I) |
| INSTALLATION ORIENTATION: | Ceiling Mount | IP RATING: | IP20 |
| CUT OUT HOLE: | 76mm/3" | BATHROOM ZONE: | Zone 3 |
| RECESS DEPTH: | 150 (mm) | VOLTAGE: | Mains 230 (V) |
| FIRE RATING: | Not Applicable | PRODUCT F MARK: | Not suitable for mounting on flammable materials. Not suitable for covering with thermal materials. |

LAMP

| | | | |
|-----------------------------|----------------|-----------------------------------|----------------|
| LIGHT SOURCE: | GU10 | MACADAM ELLIPSE: | Not Applicable |
| MAXIMUM WATTAGE: | Lamp Dependent | UGR: | Not Applicable |
| MAXIMUM LAMP LENGTH: | 75 (mm) | BEAM ANGLE: | Lamp Dependent |
| LAMP INCLUDED? | No | TILT ADJUSTMENT ANGLE: | Not Applicable |
| LUMINOUS FLUX: | Lamp Dependent | ROTATION ADJUSTMENT ANGLE: | Not Applicable |
| COLOUR TEMP: | Lamp Dependent | AVERAGE LIFESPAN: | Lamp Dependent |
| CRI: | Lamp Dependent | L70: | Not Applicable |
| R9: | Lamp Dependent | | |

ELECTRICAL

| | | | |
|-------------------------------|----------------|-----------------------------------|----------------|
| SWITCHED: | No | SUPPLY FREQUENCY: | Not Applicable |
| DIMMABLE: | Yes | DRIVER / BALLAST VOLTAGE: | Not Applicable |
| DIMMING METHOD: | Lamp Dependent | DRIVER AVERAGE LIFESPAN: | Not Applicable |
| DRIVER OUTPUT CURRENT: | Not Applicable | EFFICACY: | Lamp Dependent |
| DRIVER OUTPUT VOLTAGE: | Not Applicable | DRIVER / BALLAST INCLUDED? | Not Applicable |

ADDITIONAL INFORMATION



BOX QUANTITY x 60

PRODUCT ELEVATIONS

