

SIRRO

03-Aug-2018

2.0 LED - ceiling surfaced

LED 2x10W | 220-240VAC | 50-60Hz | COB 3-step | incl. PS | phase-cut dim

CE IP20 0,3m 36° 35°/35° 355°

white texture	139264W_
white texture + black	139264E_
aluminium brushed + black	139264F_
black texture	139264B_

LIGHT COLOUR

2700K >90CRI 590lm	3
3000K >90CRI 640lm	5
1800-2850K >95CRI 440lm	9

2.0 PAR16 - ceiling surfaced

2xPAR16 max. 35W | GU10 | 100-240VAC | 50-60Hz

CE IP20 0,3m 35°/35° 355°

white texture	139220W0
white texture + black	139220E0
aluminium brushed + black	139220F0
black texture	139220B0

OPTIONAL

for PAR16 lamps see our catalogue

2.0 LED - suspended

LED 2x10W | 220-240VAC | 50-60Hz | COB 3-step | incl. PS | phase-cut dim

CE IP20 0,3m 36° 35°/35° 355°

white texture	139664W_
white texture + black	139664E_
aluminium brushed + black	139664F_
black texture	139664B_

LIGHT COLOUR

2700K >90CRI 590lm	3
3000K >90CRI 640lm	5
1800-2850K >95CRI 440lm	9

2.0 PAR16 - suspended

2xPAR16 max. 35W | GU10 | 100-240VAC | 50-60Hz


CE IP20 0,3m 35°/35° 355°

white texture	139620W0
white texture + black	139620E0
aluminium brushed + black	139620F0
black texture	139620B0



OPTIONAL

for PAR16 lamps see our catalogue



②



③




④




* wired spring version from inset also compatible

⑤




⑥




DIMENSIONS

CEILING SURFACED




SUSPENDED



MOUNTING INSTRUCTION

POWER CONNECTION

① PARALLEL CONNECTION - for LED and PAR16



② Mount the ceiling base on the ceiling

③ Attach the SIRRO to the ceiling base (in case of surfaced version)

④ Insert the outer part of the inset module into the SIRRO

⑤ Insert the lamps into the inner parts of the inset module

⑥ Click the inner part of the inset module into the outer part



WEVER & DUCRÉ
LIGHTING

www.weverducre.com

Wever & Ducre bvba Spinnerijstraat 99/21 8500 Kortrijk

INSTALLATION
INSTRUCTIONS