

**WINK ASY 82 LED GE**


Wink may be recessed, and therefore discreet, but its technical ingenuity is nothing short of remarkable, so is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon. With the debut of the Wink 82, we are also presenting a completely new Wink accessory: Wink flange. Compatible with all 3 Wink lamps, Wink flange adds an extra accent in the form of a low ring around the spot, rather than a completely seamless install. Its precision-designed conical shape complements the spot, enabling it to have a quiet conversation with the ceiling.

Art. Nr. 14201432

**SPECIFICATIONS**

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 98 h 100 (Wink Flange) or ø 111 h 100 (Recessed ring)	
Weight	0.29kg	
Min. distance	0.1 m	
IP	IP54	
Glow wire test	960°	
Lifetime	L80 B20 @ 50.000 hrs	
CRI	90	
Power supply	350mA	<b>500mA</b>
	17.8Vf	<b>18.4Vf</b>
Connected load	6.2W	<b>9.2W</b>
Lumen	458lm	<b>615lm</b>
Efficacy	74lm/W	<b>67lm/W</b>
UGR	19	<b>20</b>
Adjustability	h 360°	
Remark	! must be used with recessed ring or flange ! LED light is inserted at a 30° angle	

	WARM WHITE 2700K / CRI 90+			WARM WHITE 3000K / CRI 90+		
	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°
black struc	14201032	14201132	14201232	14201332	<b>14201432</b>	14201532
white struc	14201009	14201109	14201209	14201309	14201409	14201509



Available label  
<http://supemodular.com/assets/TYPE2.pdf>



---

## WINK ASY 82 LED GE

---

### ACCESSORIES

#### HUE-BRIDGE

---

70000616	HUE BRIDGE EU
----------	---------------

#### HUE-DEVICE

---

70000152	HUE DIMMER SWITCH
----------	-------------------

70000615	HUE TAP SWITCH
----------	----------------

70008054	HUE SENSOR
----------	------------