





LOTIS 82 MR16 GE

Lotis is the recessed spotlight which started it all. The hallmark of this luminaire, is the deeply recessed cone which holds the light source and has a fine edge. Lotis comes in different diameters and with different lighting sources. Lotis 48 is particularly fitted to use in wall mounted application.

Art. Nr. 10880146 SPECIFICATIONS 1x QR-CBC 51 Gx5.3 max. 50W Lamp Gear / Transfo transfo not incl. Cut-out size ø 76 h 130 Weight 0.1kg Min. Distance 0.5 m Power supply 12V ΙP IP20 Glow Wire Test 960° CRI 100 644 Lm Lumen 14 Lm/W Efficacy UGR 10 Adjustability Not Applicable This label is available in other languages: http://supermodular.com/assets/TYPE3.pdf MODULAR. This luminaire is compatible with bulbs of the energy classes: 874/2012

alu	10880105
black	10880102
gold	10880146
white struc	10880109

Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.

LOTIS



LOTIO DO MD40 OF				
LOTIS 82 MR16 GE				
ACCESSORI CONBOX	E)			
	CONDOX 100V100V120V2EC			
10889830	CONBOX 190X192X130X256			
GYPKIT				
12290830	GYPKIT 190X190 - Ø76			

28/11/2016 - ©2016 Modular Lighting Instruments