


## MÉDARD RECESSED 42 LED GE

Médard recessed broadens the variety of applications. In contrast to the rest of the family, Médard recessed's light source is fixed, emanating a medium or flood beam angle. Hospitality environments including wellness centers, and high-end residential spaces, including bathrooms, will be spot-on locations for this IP55-rated new family member.

Art. Nr. 11550232

### SPECIFICATIONS

Lamp	1x LED Module	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 40 h 65	
Weight	0.11kg	
Min. distance	0.1 m	
IP	IP55	
Glow wire test	960°	
Lifetime	50000 hrs	
CRI	90	
CIE flux code	100/100/100/100/76	
Power supply	350mA	<b>500mA</b>
	8.5Vf	<b>8.8Vf</b>
Connected load	3W	<b>4.3W</b>
Lumen	259lm	<b>349lm</b>
Efficacy	86lm/W	<b>81lm/W</b>
UGR	11	<b>12</b>
Adjustability	Not Applicable	



Available label  
<http://supemodular.com/assets/TYPE2.pdf>

	WARM WHITE 2700K / CRI 90+		WARM WHITE 3000K / CRI 90+	
	MEDIUM 25°	FLOOD 40°	MEDIUM 25°	FLOOD 40°
black struc	11550032	11550132	<b>11550232</b>	11550332
white struc	11550009	11550109	11550209	11550309



## MÉDARD RECESSED 42 LED GE

### ACCESSORIES

#### HUE-MODULE

13190130 | HUE DIM CIRCUIT MODULE 150-300W 0/1-10V

#### HUE-BRIDGE

70000616 | HUE BRIDGE EU

70000617 | HUE BRIDGE UK

#### HUE-DEVICE

70000615 | HUE TAP SWITCH

70000154 | NIKO PURE SWITCH FOR HUE - WHITE STEEL

70000155 | NIKO PURE SWITCH FOR HUE - BLACK STEEL

70000152 | HUE DIMMER SWITCH

70008054 | HUE SENSOR

