

BAYVILLE SPIKE SPOT 12V 8310

SKU 1401009

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	Textured Black	CABLE LENGTH:	2000 (mm)
MAIN MATERIAL:	Metal - Aluminium	GROSS WEIGHT:	0.87 (Kg)
DIMENSIONS:	H: 94mm W: 75mm D: 102mm	CLASS:	CE (Class III)
INSTALLATION ORIENTATION:	Ground/Floor	IP RATING:	IP65
CUT OUT HOLE:	Not Applicable	BATHROOM ZONE:	Zone 1, 2, 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	12V
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:	LED	MACADAM ELLIPSE:	To Be Advised
MAXIMUM WATTAGE:	5W	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	35 (Degrees)
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	90 (Degrees)
LUMINOUS FLUX:	465 (lm)	ROTATION ADJUSTMENT ANGLE:	330 (Degrees)
COLOUR TEMP:	3000 (K)	AVERAGE LIFESPAN:	To Be Advised
CRI:	80	L70:	To Be Advised
R9:	5.1		


ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	Not Applicable
DIMMABLE:	Yes	DRIVER / BALLAST VOLTAGE:	Not Applicable
DIMMING METHOD:	Phase - Leading & Trailing Edge	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	Not Applicable
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER / BALLAST INCLUDED?	Not Applicable

ADDITIONAL INFORMATION

CE

Product tested with 1613 - LED Driver CV 12V 20W



BOX QUANTITY x 12

PRODUCT ELEVATIONS

GB Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.

FR Veuillez noter que certaines dimensions peuvent varier légèrement en raison des tolérances de fabrication, y compris l'entrée de câble et les trous de fixation.

DE Bitte beachten Sie, dass die Maße Fertigungstoleranzen unterliegen und daher in geringem Umfang von der angegebenen Größe abweichen können. Dies gilt auch für Kabeleingänge und Befestigungslöcher.

IT Si prega notare che possono esserci piccole variazioni in alcune dimensioni dovute alle tolleranze di produzione, queste includono l'ingresso del cavo e i fori di fissaggio.

