

HOLLOW 125 LED GE


For designer James Van Vossel, it was time to rethink pure, simple forms. That's when the tube came in. And out. Hollow reignites the excitement and mystery surrounding this classical shape. How does it work? Where's the light coming from? Hollow won't be revealed until you touch it. Lit, dark, open, closed. A symphony of opposites, adjustable and versatile. For spaces that welcome intrigue and personality. It's the light to discover.

Art. Nr. 12171109

SPECIFICATIONS

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 115 h 70	
Weight	0.27kg	
Min. distance	0.1 m	
IP	IP20	
Glow wire test	960°	
Lifetime	L80 B20 @ 50.000 hrs	
CRI	90	
CIE flux code	92/99/100/100/48	
Power supply	350mA	500mA
	16.4Vf	16.9Vf
Connected load	5.7W	8.5W
Lumen	353lm	476lm
Efficacy	62lm/W	56lm/W
UGR	13	14
Adjustability	h 360° v 90°	

	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
	LENS 30°	LENS 30°
black struc - black struc	12171056	12171156
black struc - gold	12171032	12171132
black struc - white struc	12171047	12171147
gold - gold	12171087	12171187
white struc - white struc	12171009	12171109



Available label
<http://supemodular.com/assets/TYPE2.pdf>



HOLLOW 125 LED GE

ACCESSORIES

HUE-MODULE

13190130 | HUE DIM CIRCUIT MODULE 150-300W 0/1-10V

HUE-BRIDGE

70000616 | HUE BRIDGE EU

70000617 | HUE BRIDGE UK

HUE-DEVICE

70000615 | HUE TAP SWITCH

70000154 | NIKO PURE SWITCH FOR HUE - WHITE STEEL

70000155 | NIKO PURE SWITCH FOR HUE - BLACK STEEL

70000152 | HUE DIMMER SWITCH

70008054 | HUE SENSOR

CONBOX

10889830 | CONBOX 190X192X130X256

