

# FLOS


F015K32B006 Grey

## Mile Bollard 2 900 Double Dimmable 1-10V NEW

Designed by Antonio Citterio



LED light source included. Integrated 220-240V ON/OFF and 1-10V or DALI dimmable electrical power. Equipped with a length of neoprene cable and an IP68 2-way anticondensation H2O stop seal system. The device may be installed on any flooring with anchors. Anchoring plate for installation on flooring laid over concrete sold separately.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                  |                      |
|------------------|----------------------|
| Mounting         | Ground               |
| Environments     | Outdoor wet location |
| LED type         | Power LED            |
| Lamp category    | LED                  |
| Number of heads  | 2                    |
| Power (W)        | 15.6                 |
| System flux (lm) | 2x627                |

### Physical

|                 |       |
|-----------------|-------|
| Colour          | Grey  |
| Orientation     | Fixed |
| Net weight (kg) | 4.8   |
| IP internal     | 65    |

### Download

[Mounting instructions](#) ZIP

### Photometric Files

[LDT / IES](#) ZIP

### Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



## Schematic light drawing



Beam Angle: 57°

| h(m) | E(lx) | D(m)  |
|------|-------|-------|
| 1    | 195   | 4.54  |
| 2    | 49    | 9.08  |
| 3    | 22    | 13.62 |
| 4    | 12    | 18.16 |
| 5    | 8     | 22.70 |

## Photometric

|                    |            |
|--------------------|------------|
| Lighting type      | Direct     |
| Light distribution | Asymmetric |
| CCT (K)            | 3000       |
| CRI>               | 80         |

## Electrical

|                    |                |
|--------------------|----------------|
| Insulation class   | I              |
| Frequency (Hz)     | 50-60          |
| Main voltage (Vac) | 220-240        |
| Driver             | Integrated     |
| Dimmable           | Yes            |
| Dimming type       | Dimmable 1-10V |
| Emergency type     | No             |

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

## Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance


## Accessories & Power Supply



OPTIONAL  
Accessory

F015Z010000

Base plate with bolt



OPTIONAL  
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION  
DEVICE)