




# RINI SNEAK IP44

CEILING RECESSED



p. 587



## 1.0 LED

LED 7/10W | 350/500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.18 kg | IP44 | 3-step | 36°

76 | 46 | 4-30

	CODE
	154261W
	154261B

### Light Colour Selection


	LUMEN	CRI	CODE
2700K	460/620	>90	3
3000K	480/640	>90	5
1800-2850K	16V 290/390	>95	9

## ALWAYS USE

power supply

	CODE
350mA   10W	90223401
500mA   10W	90214404
500mA   15W dim	90224501

more power supplies on page 588



## 1.0 MR16

QR-CBC51 max. 35W | GU5.3  
12V | excl. power supply  
aluminium powder coated

0.12 kg | IP44 | 0.9-D

76 | 55 | 4-30


	CODE
	154210W0
	154210B0

## ALWAYS USE

power supply

	CODE
12V   10W dim	90221401
12V   25W dim	90221701
12V   70W dim	90221904

more specs on page 591



## 1.0 PAR16

PAR16 max. 35W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.16 kg | IP44 | 0.9-D

76 | 80 | 4-30

	CODE
	154220W0
	154220B0

## OPTIONAL

PAR16 LED GU10 7W  
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 593