

## THIMBLE 74 LED GE

Thimble evokes minimalism, surprise and technology all at once. Subtle curves, slightly revealing colours, high-quality lens and LED. With its deep-recessed and glare-free light source, Thimble's clean and seamless execution makes it a quiet yet sophisticated choice for high-end residential or hospitality settings. This versatile, elegant architectural downlighter will bring pure form, definition and quality light to any space without stealing all the attention.


Art. Nr. 11620041

### SPECIFICATIONS

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 70 h 100	
Weight	0.25kg	
Min. distance	0.1 m	
IP	IP55	
Glow wire test	960°	
Lifetime	50000 hrs	
CRI	90	
Power supply	350mA	500mA
	16Vf	16.2Vf
Connected load	5.6W	8.1W
Lumen	493lm	680lm
Efficacy	88lm/W	84lm/W
UGR	1	
Adjustability	Not Applicable	

Available label  
<http://supemodular.com/assets/TYPE2.pdf>

	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
	MEDIUM 30°	MEDIUM 30°
ano black	11620081	11620181
ano bronze	11620082	11620182
ano champagne	<b>11620041</b>	11620141
ano gold	11620042	11620142
ano silver bronze	11620084	11620184
black struc	11620032	11620132
white struc	11620009	11620109



## THIMBLE 74 LED GE

### ACCESSORIES

#### CONBOX

11624130	CONBOX 140X400X100X210
11624030	CONBOX 140X250X100X210

