



DEEP ADJUST trimless

CEILING RECESSED



1.0 LED

LED COB 6/9W | 350/500mA | 17V
excl. driver
aluminium powder coated

IP20 0°-35°/355° 36° SDCM2 L80/55K 0.23kg

CODE
184861W
184861G
184861B

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	530/715	>90	3
3000K	575/775	>90	5
4000K	620/830	>90	7
2000-3000K	380/560	>90	9

ALWAYS USE


alu plasterkit 105-110 95 12.5, 15, 20, 25

CODE
90017209

driver | 500mA

	CODE
10W	90214405
10W dim	90224402
20W DALI	90244604

more options and specs on page 737



1.0 MR16

QR-CBC51 max. 12W | GU5.3 | 12V
excl. driver
aluminium powder coated

IP20 0°-35°/355° 0.17kg

CODE
112810W0
112810G0
112810B0

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	460lm	>90	3
2700K	437lm	>90	3
3000K	500lm	>90	5
3000K	457lm	>90	5

ALWAYS USE


alu plasterkit 105-110 95 12.5, 15, 20, 25

CODE
90017209

driver | 12V

	CODE
10W dim	90221401
25W dim	90221701
70W dim	90221904

specs on page 739



1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

IP20 0°-35°/355° 0.21kg

CODE
112820W0
112820G0
112820B0

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	460lm	>90	3
2700K	437lm	>90	3
3000K	500lm	>90	5
3000K	457lm	>90	5

ALWAYS USE

alu plasterkit 105-110 110 95 12.5, 15, 20, 25

CODE
90017209

driver | 12V

	CODE
2700K 460lm	901228W3
2700K 437lm	901228B3
3000K 500lm	901228W5
3000K 457lm	901228B5

more lamps and specs on page 743



Rev. 001/2023-08