




2612

Design By Arik Levy

Wall light that marks coordinates with a rectilinear language, connects points of light in space, relates planes and underlines the architectural dimension. Indirect lighting and composition based on volumes clarify light and shade.

Model Sheet




Finish	21 Black Grey NCS S 7000-N
	15 Grey L2 NCS S 2500-N
LED temperature color	3000 K / 3500 K / 4000 K
Dimming	DALI / 1-10V / CASAMBI
Installation type	Surface Canopy
Materials	Body: Aluminum Diffuser: Polycarbonate Profile: Aluminum
LED	 CRI>90 3000 K / 3500 K / 4000 K
Driver	Constant Voltage 110-240 V V 50-60 Hz HZ
Remarks	Only one main input by square box 16x16cm.
	  Dimmable LED
	IP20 Bi-volt 50-60Hz 1-10V
Application	Wall Lamps
Packaging	2 Box 0.224 m x 0.325 m x 0.37 m Gross weight 5 Net weight 2.664 Vol. 0.0384

Lighting effect

General Lighting


Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



Photometric Data

Efficiency	100.00%
Coordinate System	CG
Total Flux	378.81 lm
Maximum Value	166.08 cd

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com