

Date \_\_\_\_\_

\_\_\_\_\_

Name \_\_\_\_\_

\_\_\_\_\_

Client \_\_\_\_\_

\_\_\_\_\_

Project name \_\_\_\_\_

\_\_\_\_\_

Quote# \_\_\_\_\_

\_\_\_\_\_


Type/Quantity \_\_\_\_\_

\_\_\_\_\_

05/11/2018 14:58:57

**WIRELESS CONTROL DIM8**  
**300 90 004 ED8**

[Weblink](#)



Cutout shape/size: 40 mm

MAX.MAINS CURRENT 0,65A

TRAILING EDGE PHASE CONTROL

MAX. OUTPUT POWER:

- INCANDESCENT & MAINS HALOGEN: 150W @ 230V / 70W @ 110V
- dimmable MAINS LED (no control gear): 150W @ 230V / 70W @ 110V
- HALOGEN 12V (electronic transformer): 50W @ 230V / 25W @ 110V
- LED (dimmable power supply): 50W @ 230V / 25W @ 110V

Electrical 110-240V / 50-60Hz

Class: II

Weight: 0.15 KG

Protection level: IP20

Minimum distance: n.a.

Remarks: [Click here for more information concerning Wireless Control by CTRL DELTA](#)

For detailed installation instructions, please consult the manual. [300\\_90\\_004\\_ED8\\_HAND.pdf](#)