

# FLOS

09.3201.BZA Bronze

## G-O Amber Light

Designed by Jorge Herrera, 2017



Semi recessed signalling lamp for indoor use on ceiling/wall. Power supply not included. 1000 mm power cable included.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Wall recessed
Environments	Indoor dry location
LED type	Top LED
Lamp category	LED
Number of heads	1
Power (W)	1.2
Source flux (lm)	96
System flux (lm)	2

### Physical

Colour	Bronze
Trim	No
Orientation	Fixed
Recessed depth (mm)	56
Net weight (kg)	0.2
IP internal	20
IP external	65



### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)




### Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional

## Schematic light drawing



Beam Angle:	72°		
h(m)	E(lx)	D(m)	
1	1	1.46	
2	0	2.92	
3	0	4.38	
4	0	5.85	
5	0	7.31	

### Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	3000
Beam angle C0-180 (°)	72
Beam angle C90-270 (°)	72
UGR <sub>L</sub>	14

### Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	25
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable DALI 1

### Notes

Equipment for remote installation in an accessible place: it does not fit through the luminaire installation hole. For Dali installation, the non-dimmable kit and the Dali controller are needed.

## Accessories & Power Supply



REQUIRED  
Power supply

Electrical

60.9157

Electronic transformer with constant voltage (24V) for LED. 8W, 110/240V, 50/60H



REQUIRED  
Power supply

Electrical

60.8703

Electronic transformer with constant voltage (24V) for LED. 100/240V. 25W



OPTIONAL  
Accessory

08.8422.00

Prepared for recessing



OPTIONAL  
Accessory

Electrical

60.8640

Control Unit 1-10V



OPTIONAL  
Accessory

Electrical

60.9766

Control Unit DALI



OPTIONAL  
Control interface

Electrical

60.9678A

LED module Dali/Push dimmable control unit for 12, 24 or 48Vdc