



FLAT MOON 650 CEILING DOWN LED DALI/PUSHDIM GI

Contemporary architectural projects love a minimalist, slim lighting design. Flat moon is a stylish, reduced height fixture (78 mm) that distributes a soft, yet functional light. Office-compliant when combined with one of the prismatic diffusers, it is also a perfect fit for public spaces, hotels, restaurants or retail environments. Exceptionally versatile, Flat moon can be either surface-mounted, recessed or suspended (with two types of suspension kits for either down or up/down lighter) and even directly mounted and connected onto the gear. It comes in three sizes: 450, 650 or 950 mm diameter.

Art. Nr. 13292532

SPECIFICATIONS

| | |
|----------------|----------------------|
| Gear / Transfo | LED gear incl. |
| Weight | 10.7kg |
| Min. distance | 0.1 m |
| Power supply | 230V |
| IP | IP20 |
| Glow wire test | 650° |
| Lifetime | L80 B20 @ 50.000 hrs |
| CRI | 90 |
| CIE flux code | 47/78/95/100/72 |
| Lumen | 6389 Lm |
| Efficacy | 91 Lm/W |
| UGR | 23 |
| Adjustability | Not Applicable |

Available label
<http://supemodular.com/assets/TYPE2.pdf>

| | WARM WHITE 2700K / CRI 90+ | WARM WHITE 3000K / CRI 90+ | WARM WHITE 4000K / CRI 90+ |
|-------------|-------------------------------|-------------------------------|-------------------------------|
| black struc | 13292332 | 13292432 | 13292532 |
| white struc | 13292309 | 13292409 | 13292509 |

