



## PRODUCT SPECIFICATION

### GENERAL

|                                  |                           |                        |  |
|----------------------------------|---------------------------|------------------------|--|
| <b>FINISH:</b>                   | Antique Brass             | <b>CABLE LENGTH:</b>   | Not Applicable                                   |
| <b>MAIN MATERIAL:</b>            | Metal - Mild Steel        | <b>GROSS WEIGHT:</b>   | 1.11 (kg)  |
| <b>DIMENSIONS:</b>               | H: 56mm W: 760mm D: 210mm | <b>CLASS:</b>          | CE (Class I)                                     |
| <b>INSTALLATION ORIENTATION:</b> | Wall Mount - Horizontal   | <b>IP RATING:</b>      | IP20   |
| <b>CUT OUT HOLE:</b>             | Not Applicable            | <b>BATHROOM ZONE:</b>  | Zone 3   |
| <b>RECESS DEPTH:</b>             | Not Applicable            | <b>VOLTAGE:</b>        | Mains 230 (V)                                    |
| <b>FIRE RATING:</b>              | Not Applicable            | <b>PRODUCT F MARK:</b> | Not suitable for mounting on flammable materials |

### LAMP

|                             |                |                                   |                |
|-----------------------------|----------------|-----------------------------------|----------------|
| <b>LIGHT SOURCE:</b>        | Mid-Power LED  | <b>MACADAM ELIPSE:</b>            | 3-Step         |
| <b>MAXIMUM WATTAGE:</b>     | 8W             | <b>UGR:</b>                       | To Be Advised  |
| <b>MAXIMUM LAMP LENGTH:</b> | Not Applicable | <b>BEAM ANGLE:</b>                | Not Applicable |
| <b>LAMP INCLUDED?</b>       | Yes            | <b>TILT ADJUSTMENT ANGLE:</b>     | 90 (Degrees)   |
| <b>LUMINOUS FLUX:</b>       | 652.20 (lm)    | <b>ROTATION ADJUSTMENT ANGLE:</b> | Not Applicable |
| <b>COLOUR TEMP:</b>         | 2700 (K)       | <b>AVERAGE LIFESPAN:</b>          | Not Applicable |
| <b>CRI:</b>                 | 70             | <b>L70:</b>                       | To Be Advised  |
| <b>R9:</b>                  | 6.7            |                                   |                |

### ELECTRICAL

|                               |                |                                   |                |
|-------------------------------|----------------|-----------------------------------|----------------|
| <b>SWITCHED:</b>              | No             | <b>SUPPLY FREQUENCY:</b>          | 50/60 (Hz)     |
| <b>DIMMABLE:</b>              | No             | <b>DRIVER / BALLAST VOLTAGE:</b>  | 100-240 (V)    |
| <b>DIMMING METHOD:</b>        | Not Applicable | <b>DRIVER AVERAGE LIFESPAN:</b>   | 30,000 (hrs)   |
| <b>DRIVER OUTPUT CURRENT:</b> | Not Applicable | <b>EFFICACY:</b>                  | 51.8 (lm/W)    |
| <b>DRIVER OUTPUT VOLTAGE:</b> | 12 (V)         | <b>DRIVER / BALLAST INCLUDED?</b> | Yes (Integral) |

## ADDITIONAL INFORMATION



BOX QUANTITY X 12

# PRODUCT ELEVATIONS

---

