



F015E41D033 Anthracite

Mile Wall 2 Washer Up Dimmable DALI NEW

Designed by Antonio Citterio






LED - Power LED - 6.4W - 489lm - 4000K - CRI> 80

LED light source included. Integrated 220-240V ON/OFF and 1-10V or DALI dimmable electrical power. Equipped with double cable gland for electrical connection.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall	
Environments	Outdoor wet location	
LED type	Power LED	
Lamp category	LED	
Number of heads	1	
Power (W)	6.4	
System flux (lm)	489	

Physical

Colour	Anthracite	
Orientation	Fixed	
Net weight (kg)	0.8	
IP internal	65	

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings

2D	<u>↓</u> ZIP
3D	⊥ ZIP
a Bim	↓ ZIP













https://professional.flos.com/en/global/product/mile-wall-2-washer-up-dimmable-dali-f015e41d033/

F015E41D033

Schematic light drawing



Beam	Beam Angle:	
h(m)	E(lx)	D(m)
1	132	3.53
2	33	7.06
3	15	10.59
4	8	14.12
5	5	17.66

Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	4000
CRI>	80

Electrical

Insulation class	I	
Frequency (Hz)	50-60	
Main voltage (Vac)	220-240	
Driver	Integrated	
Dimmable	Yes	
Dimming type	Dimmable DALI 1	
Emergency type	No	

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL Accessory

F990E00A000

S.P.D. (SURGE PROTECTION DEVICE)