

FLOS

■ F4640030 Black

OK

Designed by Konstantin Grcic, 2014


18W - 1551lm - 2700K



Lamp providing direct light. Head in gloss varnished. Body in injection-stamped PA66+30%FV with cover in gloss varnished. Orientable head. The light fitting can be moved vertically by running the internal structure of the body on a steel cable tensioned between the ceiling and the floor (useful length 4000mm). Dimmable switch with Soft Touch technology. Adaptor on plug connector with interchangeable plugs.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8059607005064
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	18
System flux (lm)	1551

Physical

Colour	Black
Length (mm)	200
Cord length (mm)	4000
Canopy dimension (mm)	20
Canopy width (mm)	64
Net weight (kg)	2.9
Package height (mm)	140
Package width (mm)	340
Package length (mm)	390
Package volume (m3)	0.02
IP internal	20

Download

Mounting instructions	↓ PDF
Mounting instructions	↓ PDF
Spare Parts	↓ PDF

Photometric Files


LDT / IES	↓ LDT
-----------	-----------------------

Technical Drawings

2D	↓ ZIP
3D	↓ ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/24
LED voltage Vf (Vdc)	null
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 24V
Dimming interface	Dimmer Integrated
Plug type	Type G, Type A, Type C
Batteries inside	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F




Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts



01.	Black ceiling rose	RF23030
02.	Anchor with hook	RF4640100
03.	Steel cable 4mt.	RF4640200
03.	Steel cable 6mt.	RF4640300
04.	Internal lamp body assembly	RF4640400
05.	Black extrusion	RF22996
06.	Black led head assembly	RF28254
07.	Hex Key 2mm for OK lamp	RF06850
08.	Counterweight	RF23023
09.	Black plug assembly kit & 24V driver	RF3320100

DOWNLOAD



RF23030
Black ceiling rose



RF4640100
Anchor with hook



RF4640200
Steel cable 4mt.



RF4640300
Steel cable 6mt.



RF4640400
Internal lamp body assembly



RF22996
Black extrusion



RF28254
Black led head assembly



RF06850
Hex Key 2mm for OK lamp



RF23023

Counterweight



RF3320100

Black plug assembly kit & 24V driver